



双列角接触球轴承滚轮



3057...2Z
3067...2Z



3058...2Z
3068...2Z

型号		外形尺寸					极限 转速	额定负荷				允许最大负 荷		重量
圆柱外径	球面外径	D	d	B	R	r1,r2 min	min-1	作轴承时		作滚轮时		动负 荷	静负 荷	
								动负 荷	静负 荷	动负 荷	静负 荷			
305700.2Z	305800.2Z	32	10	14	400	0.6	13000	7.8	4.5	7.4	4.1	9	12.9	0.062
305700.2RSR	305800.2RSR	32	10	14	400	0.6	8500	7.8	4.5	7.4	4.1	9	12.9	0.062
305701.2Z	305801.2Z	35	12	15.9	400	0.6	11000	10.6	5.9	10	5.2	8.3	12	0.078
305701.2RSR	305801.2RSR	35	12	15.9	400	0.6	7300	10.6	5.9	10	5.2	8.3	12	0.078
305702.2Z	305802.2Z	40	15	15.9	400	0.6	10000	11.9	7.1	11.1	6.4	12.2	17.6	0.1
305702.2RSR	305802.2RSR	40	15	15.9	400	0.6	6500	11.9	7.1	11.1	6.4	12.2	17.6	0.1
305703.2Z	305803.2Z	47	17	17.5	400	0.6	9000	14.6	9	13.8	8.3	19.3	27.5	0.16
305703.2RSR	305803.2RSR	47	17	17.5	400	0.6	6000	14.6	9	13.8	8.3	19.3	27.5	0.16
306702.2Z	306802.2Z	47	15	19	400	1	10000	17.7	10.3	14.6	9.2	12.5	18.4	0.15
306702.2RSR	306802.2RSR	47	15	19	400	1	6500	17.7	10.3	14.6	9.2	12.5	18.4	0.15
305704.2Z	305804.2Z	52	20	20.6	400	1	8000	19.5	12.5	18.2	11	17	18.4	0.15
305704.2RSR	305804.2RSR	52	20	20.6	400	1	5300	19.5	12.5	18.2	11	17	18.4	0.15
306703.2Z	306803.2Z	52	17	22.2	400	1	9500	21.1	12.5	17.2	11	15.5	22.2	0.2
306703.2RSR	306803.2RSR	52	17	22.2	400	1	6300	21.1	12.5	17.2	11	15.5	22.2	0.2
305705.2Z	305805.2Z	62	25	20.6	400	1	7000	21.2	14.6	19.9	13.4	30.5	44	0.32
305705.2RSR	305805.2RSR	62	25	20.6	400	1	4500	21.2	14.6	19.9	13.4	30.5	44	0.32
306704.2Z	306804.2Z	62	20	22.2	400	1.1	9000	24.5	15.8	21.1	14.5	27	29	0.34
306704.2RSR	306804.2RSR	62	20	22.2	400	1.1	6000	24.5	15.8	21.1	14.5	27	29	0.34
305706.2Z	305806.2Z	72	30	23.8	400	1	6000	29.6	21.2	27.6	18.6	34	49	0.49
305706.2RSR	305806.2RSR	72	30	23.8	400	1	4000	29.6	21.2	27.6	18.6	34	49	0.49
306705.2Z	306805.2Z	72	25	25.4	400	1.1	7900	32.5	21.6	27.5	19.5	34.5	39	0.5

双列角接触球轴承滚轮

306705.2RSR	306805.2RSR	72	25	25.4	400	1.1	5200	32.5	21.6	27.5	19.5	34.5	39	0.5
305707.2Z	305807.2Z	80	35	27	400	1.1	5300	39	28.5	35.1	24	31	44	0.65
305707.2RSR	305807.2RSR	80	35	27	400	1.1	3500	39	28.5	35.1	24	31	44	0.65
306706.2Z	306806.2Z	80	30	30.2	400	1.1	6200	45.5	31.5	36.5	26.5	43.5	53	0.67
306706.2RSR	306806.2RSR	80	30	30.2	400	1.1	4100	45.5	31.5	36.5	26.5	43.5	53	0.67
305708.2Z	305808.2Z	85	40	30.2	400	1.1	5000	50	37.5	34.5	22.5	208.8	36	0.75
305708.2RSR	305808.2RSR	85	40	30.2	400	1.1	5000	50	37.5	34.5	22.5	208.8	36	0.75
306707.2Z	306807.2Z	90	35	34.9	400	1.5	5100	56	39.5	44.5	33	39.5	66	0.95
306707.2RSR	306807.2RSR	90	35	34.9	400	1.5	2400	56	39.5	44.5	33	39.5	66	0.95
306708.2Z	306808.2Z	100	40	36.5	400	1.5	4700	69	49.5	56	42	70	84	1.2
306708.2RSR	306808.2RSR	100	40	36.5	400	1.5	4700	69	49.5	56	42	70	84	1.2